

BEAM LIGHT



User Manual

Please read this manual before installing & using, and keep it for further consultation

Catalogue

Introduction.....	2
Features	
Description of the fixture	
Safety Instructions.....	2-4
The safety guides	
The operation limits	
Installation.....	4-6
Fitting/Exchanging the lamp	
Beam path	
Inserting/Exchange the gobos	
Rigging	
DMX512 connection/connection between fixtures	
DMX Channels.....	7
Display and operating instructions	
DMX 20 channels instruction	
Addressing.....	7-8
Control	
Technical Specifications.....	8-9
Power supply	
Lamp	
Color-wheel	
Fixed gobo wheel	
Rotating gobo wheel	
8/16-facet rotating prism(Optional)	
Shutter	
Focus	
Dimmer/shutter/strobe	
Fans	
Maintenance and Cleaning.....	9-10

CAUTION!

Keep this device away from rain and moistener! Unplug mains lead before opening the housing! For your own safety, please read this user manual carefully before you

initial start-up!

Introduction

Thank you for choosing our moving head light. You acquired a versatile, powerful and intelligent lighting-effect. Please unpack your casing and make sure that there are no damages caused by transportation. Should there be any, please refer to your local dealer or our factory and do not take the device into operation.

Multifid-function moving head light trait:

- Color system: One color wheel with seven kinds of different color diachronic filters plus white
- One gobo wheel with six rotating metal gobos and one glass gobo, rotating gobo can rotate to 360°
- High speed 8/16-facet rotating prism(Optional)
- Combined shutter/dimmer unit allowing very smooth dimming and strobe effect 1-10 flash/second
- The lighting of the stock size
- Addressing, special functions setting, effects calibration via control panel with LCD TOUCH SCREEN.
- Readout fixture and lamp usage, receiving DMX values, temperature, etc
- Macro-function for rotating gobo/rotating prism combinations
- Black out while the light head moving or gobo color changing
- Remote reset function
- Intelligent control panel with LCD TOUCH SCREEN.
- Silent fans cooling
- 20 DMX channels
- Pan movement rang 530°, Tilt movement rang 280°
- High luminous-efficiency parabolic mirror and double condenser system
- Mechanical multi-step focus
- Focus is controllable through the mechanization of DMX
- Preprogrammed changeable or stochastic grating pulse effect
- All lenses are anti-reflection coated
- 9 high quality stepper-motors for smooth movement
- Self-resettable therme-fuse
- For ORIGINAL OSRAM 7R 230W lamp

Safety Instructions

CAUTION ! Be careful with your operations. With a dangerous voltage you can suffer a dangerous electric shock when touching the wire!

This device has left our premises in absolutely perfect condition. In order to maintain this condition and to ensure a safe operation, it is absolutely necessary for the user to

follow the safety instructions and warning notes written in this user manual.

Important statement:

Damages caused by the disregard of this user manual are not subject to warranty. The dealer will not accept liability for any resulting defects or problems.

- If the device has been exposed to drastic temperature fluctuation, (e.g. after transportation), do not open the light at once. The agglomeration of vapor is likely destroying your product. Do not open the product until it reach normal temperature.
- This device falls under protection class 1. The power plug must only be plugged into a protection class 1 outlet. Never let the power cord come into contact with other cables! Handle the power cord all connections with the mains with particular caution!
- Make sure that the available voltage is not higher than stated on the rear panel
- Make sure that the power-cord is never crimped or damaged by sharp edges. Check the device and the power cord by the plug. Never pull out the plug by tugging the power-cord.
- Always disconnect from the mains, when the device is not in use or before cleaning it. Only handle the power cord by the plug. Never pull out the plug by tugging the power-cord.
- During the initial start-up some smoke or smell may arise. This is a normal process and does not necessarily mean that the device is defective.
- CAUTION: During the operation, the housing becomes very hot.
- Never frequently open/close the lighting for reducing the life of the lamp
- Never look directly into the light source, as sensitive persons may suffer an epileptic shock (especially meat for epileptics)!
- Damages caused by non-observance are not subject to warranty.
- Keep away children and amateurs!

Operating Determinations:

- This device is a moving-head spot for creating decorative effects. And was designed for indoor use only.
- This device is designed for professional use, for example, on stages, in discotheques, and theaters, etc.
- Lighting effects are not designed for permanent operation. Consistent operation breaks will ensure that the device will serve you for a long time without defects.
- Do not shake the device. Avoid brute force when installing or operating the device.
- Never lift the fixture by holding it at the projector head, as the mechanic may be damaged. Always hold the fixture at the transport handles.
- When choosing the installation spot, please make sure that the device is not exposed to extreme heat, moisture or dust. There should not be cables lying around. Make sure the safety of others and yours.
- Always fix the fixture with an appropriate safety-rope. Fix the safety rope at the correct holes only.
- Only operate the fixture after having checked that the housing is firmly closed and all screws are tightly fastened.
- The lamp must never be ignited if the objective lens or any housing cover is open, as

discharge lamps may expose and emit a high ultraviolet, which may cause burn.

- The maximum ambient temperature must never be exceeded.

CAUTION: The lens has to be replaced when it is obviously damaged, so that its function is impaired, e.g. dug to cracks or deep scratches.

- Operate the device only after you have familiarized with its functions. Persons not qualified are not allowed to operate the device. Most damages are the result of unprofessional operation.

CAUTION: The lamp has to be replaced when it is damaged or deformed due to the heat!

- Please use the original packing if the device is to be transported.
- Please consider that unauthorized modifications on the device are forbidden due to safety reasons.
- Never remove the serial barbal bar code from the device as this would make the guarantee void.
- If this device will be operated in any way different to the one described in this manual, the product may suffer damages and the guarantee becomes void. Furthermore, any other operation may lead to dangers like short-circuit, burns, electric shock, lamp explosion, crash.

Installation

DANGER: Install the lamp with the device switched off or unplug from mains!

Fitting/Exchanging the Lamp:

Open the small lamp cover by loosening 3 screws, open the small back cover at the back panel from the lighting, and gently pull the lamp out. If you want to change the lamp, remove the old lamp from the socket.

Do not install the lamp with a higher wattage! If so, the lamp will generate high temperatures, and the device is not designed for that case.

Damages caused by non-observance are not subject to warranty. Please follow the lamp manufacturer's announcement! Do not touch the glass bald bare handed during the installation. Make sure that the lamp is installed tightly into the lampholder.

Reinstall the top cover of the head and tighten those 4 screws.

Do not operate the fixture with operate housing-cover!

The brightness of the lighting has been aligned at the factory. Due to the difference between lamps, fine adjusted may improve light performance. Strike the lighting, open the grating and the diaphragm, adjust the brightness to 100%, then focus the light on a flat surface (e.g. wall). Through using three "A/B/C" adjusting screws, you can make the light focus on the hot spot (the brightest of the light line), Rotate one screw once to drag the hot spot through projectile shadow in the direction of diagonal. If you cannot find the hot spot, adjust the lamp until the light line is even. Through adjusting three "A/B/C" screws at the same time and deasil 1/4 rotate until the light

line distribute equably then pull the lamp into, doing so can reduce hot spot. If the light in the edge is brighter than in the center, or the light output is very low, it means the lamp is too back at the reflecting shelf. Through adjusting three "A/B/C" screws at the same time and deasil 1/4 rotate to push out the lamp until the light is bright and distribute equably.

Rigging and Hook:

- Pay attention to the safety!
- Please respectively consider the EN 60598-2-17 and the national standard during the installation! The authorized dealer must only carry out the installation.
- The installation of the projectile shelf has to be built and constructed in a way that it can hold 10 times the weight for 1 hour without any harming demolition.
- The installation must always be secured with a secondary safety attachment, e.g. an appropriate catch net. This secondary safety attachment must be constructed in a way that no part of the installation can fall down if the main attachment fails.
- When rigging, derigging or servicing the fixture staying in the area below the installation place, on bridges, under high working places and other endangered areas is forbidden.
- The operator has to make sure that the safety measure and the machine's technical installation is approved by an expert before taking into operation for the first time and after changes before taking into operation another time.
- The operator has to make sure that an expert approves safety measure and the machine's technical installation after every four years in the course of an acceptance test.
- The operator has to make sure that a technician approves the relative safety measure and the machine's technical installation once a year.
- Procedure: The projectile shelf should be installed outside areas where persons may walk by or be seated.

IMPORTANT MATTER! Overhead rigging requires extensive experience, including (but not limited to) calculating working load limits, installation material being used, and periodic safety inspection of all installation material and the projector. If you lack these qualifications, do not attempt the installation yourself, but instead use a professional structural rigger. Improper installation can result in bodily injury or property loss.

- The projectile shelf has to be installed out of the reach of people.
- If the projectile shelf shall be lowered from the ceiling or high joists, professional trussing systems have to be used. The projectile shelf must never be fixed swinging freely in the room.

CAUTION: Projectile shelf may cause severe injuries when crashing down! If you have doubted concerning the safety of a possible installation, do not install the projectile shelf!

- Before rigging make sure that the installation area can hold a minimum point load of 10 times the projector's weight.
- **DANGER OF FIRE!** When installing the device, make sure there is no highly inflammable material (decoration articles, etc.) within a distance of minimum 0.5

meter.

CAUTION ! Use two appropriate clamps to rig the fixture on the truss. Follow the instructions mentioned at the bottom of the base. Make sure that the device is fixed properly! Ensure that the structure (truss) to which you are attaching the fixtures is secure.

- The moving head light can be placed directly on the floor or rigged in any orientation on a truss without altering its operation character rustics. There are two possibilities to fix the base of the lighting, Use the rigging clamp to merge M10 or M12 screw—please check the base. For overhead use, always install a safety rope that can hold at least 10 times the weight of the fixture. You must only use safety rope with screw on carabines.

Connection with the Mains:

Connect the device to the mains with the power-plug.

The occupation of the connection-cables is as follow:

Cable	Pin	International
Brown	Live	L
Blue	Neutral	N
Yellow/green	Earth	

The earth has to be connected !

Pay attention to the safety !

Before taking into operation for the first time, the installation has to be approved by an expert !

DMX-512 Connection/Connection between Fixtures

The wires must not come into contact with each other; otherwise the fixtures will not work at all, or will not work properly.

Only use a stereo-shielded cable and 3-pin XLR-plugs/5-pin XLR-plugs and connectors in order to controller with the fixture or one fixture with another.

Occupation of the XLR Connection

DMX-output

DMX-input

XLR mounting-socket

XLR mounting-plug:

1-Ground

2-Signal (-)

3-Signal (+)

If you are using the recommended controllers, you can connect the DMX-output of the controller directly with the DMX-input of the first fixture in the DMX-chain. If you wish to connect DMX-controllers with other XLR-output, you need to use adapter-cables.

Building a Serial DMX Chain

Connect the DMX-output of the first fixture in the DMX-chain with the DMX-input of the next fixture. Always connect one output with the input of the next fixture until all fixtures are connected.

CAUTION: At the last fixture, the DMX cable has to be terminated with a terminator. Solder a 120-ohm resistor between Signal (-) and (+) into a 3-pin XLR-plug it in the

DMX-output of the last fixture.

DMX Channels

DMX Channel Description:

CHANNE L	CHANNEL MODE	
	16	20
1	PAN	PAN
2	TILT	TILT
3	PAN FINE	PAN FINE
4	TILT FINE	TILT FINE
5	DIMMER	DIMMER
6	STOP/STROBE	STOP/STROBE
7	FROST	FROST
8	FOCUS	FOCUS
9	Gobo Change	Gobo Change
10	Gobo Effect	Gobo Effect
11	COLOUR WHEEL	COLOUR WHEEL
12	COLOUR Effect	COLOUR Effect
13	PRISM INSERTION	PRISM INSERTION
14	PRISM ROTATION	PRISM ROTATION
15	PAN-TILT TIME	PAN-TILT TIME
16	Lamp_Control&Reset	Lamp_Control&Reset
17	RFU	Macro Fuction
18	RFU	COLOUR TIME
19	RFU	DIMMER-PRISM-FROST TIME
20	RFU	GOBO TIME

Addressing

The control board on the front side of the base allows you to assing the DMX fixture the address, which is defined as the first channel. For example, if you set the address to channel 5, this lighting will use the channel 5 to 16 for control

Please be sure that you do not have any overlapping channels in order to control each lighting correctly and independently from any other fixture on the DMX data link.

Addressing setting:

1. Turn on the moving head, wait till finishing the reset (RST flashes on the display).
2. The main menu is accessed by pressing the [MODE] key –press this one until the display shows message“R001”. Press [ENTER] to confirm.

3. Use the [UP] and [DOWN] keys to select the required address.

4. Press [ENTER] to confirm or press [MODE] to cancel.

Controlling:

After having addressed the lighting, you may now start operating these via your lighting controller.

Note: After switching on, the lighting will automatically detect whether DMX512 signal is received or not. If there is no signal received at the DMX input, the display will not flash.

This situation can occur if:

- The three-pin XLR plug (cable with DMX signal from controller) is not connected with the input of the moving head light.

- The controller is switched off or defective, if the cable or connector is defective or the signal wires are swap in the input connector.

Note: It's necessary to insert the XLR termination plug (with 120 Ohm) in the link in order to ensure proper transmission on the DMX data link.

Technical Specifications

Power Supply

Europe voltage: 208/230/240V AC, 50/60HZ

Fuse: T5A, 250V

The USA voltage: 100/115/208/230V AC, 50/60HZ

Lamp: OSRAM 7R

Fuse: T10A

Power consumption: 230W

Optical System

High luminous efficiency parabolic mirror and double condenser system

All lenses are anti-reflection coated

Color

Seven different colors, interchangeable dichroic filters plus white, color wheel with variable rotation speed

Gobo Rotation

Six interchangeable gobos plus white: six metal gobos, one glass gobo

Strobe

Strobe effect with variable speed (1-10 flashes per second)

Dimmer

Smooth dimmer from 0-100%

Prism

8/16-facet prism rotating in both directions at different speed

Focus

Can be controlled through DMX

Mechanical multi-step focus with three different angles (15 degree, 18 degree and 22

degree).

Shutter

Mechanical (non step can be adjusted) shutter are suitable for different line angles

Effect

Seven big prism gobos

Preprogrammed and changing shutter pulse effect

Electronics

Digital serial input DMX512

Pan movement range 530 degree

Tilt movement range 270 degree

Rigging

Stands directly on the floor

Use two clamps to install

Two truss orientation

Safety chain/cord attachment point

Temperature

Maximum ambient temperature ta: 40 degree

Maximum housing temperature tb: (steady state) 80 degree

Dimensions and Weight

Length of base (including handles): 520mm

Width: 520mm

Height (head horizontal): 700mm

Weight (net weight): 18kg

Shipping weight: 25kg

Maintenance and Cleaning

The operator must make sure that correlative safety equipment and an expert inspects machine's technical installations after every four years in the course of an acceptance test.

The operator must make sure that correlative safety equipment and machine's technical installations are inspected by a skilled technician once a year.

The following points need to be considered during the inspection:

1. All screws used for installing the devices have to be tightly connected and must not be corroded.
2. There cannot be any deformations on housing, fixations and installation spots (ceiling, suspension, trussing).
3. Mechanically moved parts like axles, eyes and others must not show any traces of wearing (e.g. material abrading or damages) and must not reate with unbalances.
4. The electric power supply cables must not show any damages, material fatigue (e.g. porous cables) or sediments. Further instructions depending on the installation spot and usage have to be adhered by a skilled installer and any safety problems

have to be removed.

Danger! High power! Danger to life!

Disconnect from mains before starting maintenance operation!

- We recommend an frequent cleaning of the device. Please use moist flax to clean. Never use alcohol or solvents.
- **CAUTION!** The lens has to be replaced when it is obviously damaged, so that its function is impaired, e.g. due to cracks or deep scratches!
- The objective lens will require weekly cleaning as smoke fluid tends to building up residues, reducing the light-output very quickly. The cooling-fans should be cleaned monthly.
- The gobos may be cleaned with a soft brush. The interior of the fixture should be cleaned at least annually using a vacuum cleaner or an air-jet.
- The dichroic color filters, the gobo-wheel and the internal lenses should be cleaned monthly.
- To ensure a proper function of the gobo-wheel, we recommend lubrication in six-month intervals. The quantity of oil must not be excessive in order to avoid that oil runs out when the gobo-wheel rotates.
- There are no serviceable parts inside the device except for the lamp and the fuse. Maintenance and service operations are only to be carried out by authorized dealers. Please refer to the "inserting and exchanging lamp" chapter in this manual.

Replacing the Fuse

If the lamp burns out, the fine-wire fuse of the device might fuse, too. Only replace the fuse of same type and rating. Before replacing the fuse, unplug mains lead.

Procedure:

STEP 1: Unscrew the fuse holder on the rear panel with a fitting screwdriver from the housing (anti-clockwise).

STEP 2: Remove the old fuse from the fuse holder.

STEP 3: Install the new fuse in the fuse holder.

STEP 4: Replace the fuse holder.

- Should you need any spare parts, please use genuine parts.
- If the power supply cable of this device becomes damaged, it has to be replaced by authorized dealers only in order to avoid hazards.
- Should you have further questions, please contact your dealer.

We hope you will enjoy your lighting. We can assure you that you will enjoy this device for years if you follow the instructions given in this manual.

Osram 230W Beam Moving Head Stage Light DMX

Bühnenbeleuchtung Licht Touch Screen

Parameter:

Spannung: AC100-240v, 50 / 60Hz

Nennleistung: 300W

Leuchtmittel: Leuchtmittel: Osram HRI 230W 7R

Farbtemperatur: 7800K Durchschnittliche Lebensdauer: 2000H

Lichtausbeute: 180000LM / 10meter

Abstrahlwinkel: Parallelstrahl Engel 0-3,8 °

Farbe: 14color + weiß, Gobo: 17 feste Gobos + leer Gobo

Effekt: Dreh 16-face Prisma, Bilaterale Dreh

Doppeldrehregenbogeneffekt, Shake-Funktion

Dimmer: 0-100% lineare Einstellung

Strobe: 0-12 mal / Sekunde.

Pan / Tilt: 540 ° / 270 ° (8/16-Bit) elektrische Korrektur

Steuermodus: DMX512 / DMX-Modus 3in XLR Basis, Master-Slave-Modus aktiviert Ton-Modus

Standalone-Modus, Auto-Modus

DMX512 Kanal: 15CH / 20ch

IP Schutzart: IP20

Paket-Größe: 42 * 47 * 58cm

Eigenschaft:

Kühlsystem: Integrierte Konvektionswärme / Luft

Fokus: Unabhängige elektronische Linienfokus

Fantasie acht Prisma Effektsteuerung

Ebene von 5400, vertikal 2700, Horizontal / Vertikal-Geschwindigkeit einstellbar

Beschreibung Trimmen (x / y-Achsen-Genauigkeit): 8/16-Bit-

Horizontale / vertikale Rückwärts

Fest Goborad: 17 Gobos, von Hochtemperatur-Sonderwerkstoffen.

Muster Wasser-Effekte.

Muster-Jitter-Effekt.

Linearer Regenbogen-Effekt

Lieferinhalt:

1x 230W Scheinwerfer

1x Steuertabellenzeile

1x Stromleitung

1x Bracket

1x Handbuch